BORSERINI

Hose Clamps



HOSE CLAMPS

PRODUCT CATALOGUE 2026

01 **LOW PRESSURE** — PAGE 1

General-purpose clips and clamps

02 **MEDIUM PRESSURE** — PAGE 3

Worm-drive and fixed-diameter clamps

03 **HIGH PRESSURE** — PAGE 4

Heavy-duty clamping solutions

04 **SPECIAL VERSIONS** — PAGE 5

Special configurations for specific applications

05 **ACCESSORIES** — PAGE 7

Components for ASFA hose clamps

Low Pressure



Two Ear Clip

W1 W4

From Ø 5–7
To Ø 43–46



Wire Clip

W1

From Ø 7.3–7.8
To Ø 19.6–20.5



Spring Clip

W1

From Ø 6
To Ø 20



Clip Clamp

W4

From Ø 8.5–9.5
To Ø 26.5–28.0



DIN 3021 Spring Band Clamp

W1

From Ø 13
To Ø 55



One Ear Clip

W1 W4

From Ø 5–7
To Ø 18–20

Low Pressure



One Ear Clip with Inner Ring

W1 W4

From Ø 7.5–8.5
To Ø 17.0–19.3



OEM Ear Clip

W1

From Ø 8.3–10.0
To Ø 62.3–65.5



Wire Clip with Screw

W1

From Ø 9.5–12.0
To Ø 76.5–84.0



Normal Mini Clip

W1

From Ø 6
To Ø 29–32



Endless Band

W2 W4

Band width
8 and 14 mm



Open Worm-Drive Clip

W2

From Ø 6–11
To Ø 11–19

Medium Pressure



ASFA High Torque (16 mm) Hose Clamp

W3 W4

From Ø 25–45
To Ø 288–310



ASFA L7 Worm-Drive Clip

W1 W2

From Ø 8–12
To Ø 25–40



Fixed Diameter S-Clamp

W1

From Ø 10
To Ø 46



ASFA S (12 mm) Hose Clamp

W1 W2 W3 W4 W5

From Ø 16–27 mm
To Ø 290–310 mm



ASFA L (9 mm) Hose Clamp

W1 W2 W3 W4 W5

From Ø 8–12 mm
To Ø 140–160 mm



ASFA S (12 mm) Hose Clamp – Black

W3

From Ø 16–27 mm
To Ø 180–200



ASFA L (9 mm) Hose Clamp – Black

W1

From Ø 8–16
To Ø 140–160 mm



SUPRA Heavy-Duty Clamp

W2 W4 W5

From Ø 17–19
To Ø 395–408



Super Heavy-Duty Clamp

W1

From Ø 17–19
To Ø 240–252



SUPRA Constant Tension Heavy-Duty Clamp

W2 W4 W5

From Ø 17–19
To Ø 239–252



SUPRA 2-Bolt Heavy-Duty Clamp

W2 W4 W5

From Ø 270–280
To Ø 820–835

Special Versions



ASFA S (12 mm) with Bridge Hose Clamp

W2 W3 W4 W5

From Ø 32–50
To Ø 220–240



ASFA L (9 mm) with Bridge Hose Clamp

W2 W3 W4 W5

From Ø 32–50
To Ø 220–240



ASFA High Torque Constant Tension Hose Clamp

W3 W4

From Ø 25–45
To Ø 210–232



TITANIUM Hose Clamp

TI

From Ø 16–27
To Ø 220–240



DIN 3016 P-Clip

W1 W4

From Ø 5
To Ø 150

Special Versions



ASFA S (12 mm) Hose Clamp with Stainless Steel Inner-Ring

W1 W2 W3 W4 W5

From Ø 16–27
To Ø 220–240



ASFA L (9 mm) Hose Clamp with Stainless Steel Inner-Ring

W1 W2 W3 W4 W5

From Ø 16–27
To Ø 220–240



ASFA Constant Tension Hose Clamp with Preassembly

W3 W4

From Ø 16–27
To Ø 80–100



ASFA S Hose Clamp with Antirotation Hole

W3 W4

From Ø 25–40
To Ø 140–160



ASFA L Hose Clamp with Antirotation Notch

W3 W4

From Ø 25–40
To Ø 140–160

Special Versions



ASFA Hose Clamp with Preassembly

W3 W4

From Ø 8–12
To Ø 220–240



ASFA S (12 mm) Hose Clamp with Stainless Steel Inner-Ring – Black

W1 W2 W3 W4 W5

From Ø 16–27
To Ø 220–240



ASFA L (9 mm) Hose Clamp with Stainless Steel Inner-Ring – Black

W1 W2 W3 W4 W5

From Ø 16–27
To Ø 220–240



ASFA S (12 mm) Constant Tension Hose Clamp

W3 W4

From Ø 8–16
To Ø 110–130



ASFA L (9 mm) Constant Tension Hose Clamp

W3 W4

From Ø 8–16
To Ø 110–130

Accessories



Safety Cap for ASFA L and S Worm-Drive Clips

Protective finishing accessory



Thumb Screw for ASFA L and S Worm-Drive Clamps

Tool-free tightening accessory



Safety Collar for ASFA L and S Worm-Drive Clamps

Protective collar accessory



www.borserini.com