MIKALOR



W4

ASFA-L (9 mm) Hose Clamp Stainless Steel W4 DIN 3017

Thanks to the exclusive design of the housing and the high- strength screw, the ASFA L Worm-Drive Clip has excellent performance while being at the same time very compact.


The cold-formed stamped 9 mm band, smoothed on the underside, combined with the bevelled band edges protects the hose from any damage.

DIN 3017. The ASFA L hose clip complies fully with the DIN 3017 norm and also with the directive EU 2002/95/EC.


*** The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.**

							Maximum Values			
Ø D Application mm	Part Number	A +0.3 -0.2	L +1 -0.5	S ±0.1	H Max.	B Max.	Pressure (Bar)	Torque (Nm)	Box Quantity	Outer Box Quantity
8-12(*)	03014000	7	18,5	0,40	9,2	11,5	15	1,5	200	1.600
8-16	03014019	9	22,1	0,65	10,5	14,0	45	3,0	200	800
12-22	03014027	9	22,1	0,65	10,5	14,0	45	3,0	200	800
16-27	03014035	9	23,6	0,75	10,5	14,0	42	3,5	200	800
20-32	03014043	9	23,6	0,75	10,5	14,0	36	3,5	200	800
25-40	03014051	9	25,6	0,75	10,5	14,0	32	4,0	100	400
30-45	03014060	9	25,6	0,75	10,5	14,0	28	4,0	100	800
32-50	03014078	9	25,6	0,75	10,5	14,0	24	4,0	100	800
40-60	03014086	9	25,6	0,75	10,5	14,0	19	4,0	100	400
50-70	03014094	9	29,6	0,75	10,5	14,0	17	4,0	100	100
60-80	03014107	9	29,6	0,75	10,5	14,0	15	4,0	100	100
70-90	03014115	9	29,6	0,75	10,5	14,0	13	4,0	50	50
80-100	03014123	9	29,6	0,75	10,5	14,0	11	4,0	50	50
90-110	03014140	9	29,6	0,75	10,5	14,0	10	4,0	25	200
100-120	03014158	9	29,6	0,75	10,5	14,0	9	4,0	25	200
110-130	03014166	9	29,6	0,75	10,5	14,0	8	4,0	25	25
120-140	03014174	9	29,6	0,75	10,5	14,0	7	4,0	25	200
130-150	03014182	9	29,6	0,75	10,5	14,0	6	4,0	25	25
140-160	03014190	9	29,6	0,75	10,5	14,0	5	4,0	25	25

(*) ASFA-L 7 mm hose clamp



TECHNICAL INFORMATION	
MATERIAL	Stainless steel band and housing W4 AISI 304 X5Cr Ni 18/10 (DIN 1.4301) Stainless steel screw W4 AISI 304
CORROSION RESISTANCE	400 hours salt spray (ASTM B-117)
MAX. TIGHTENING SPEED (RPM)	540 ± 5



Available Through BORSERINI SRL
Via C. Negri 10-12 - 23030 Chiuro (SO) - Italy | +39 0342 209200 | info@borserini.it | www.borserini.com
Registered Office: Via Parolo 38 - 23100 Sondrio (SO) - Italy