MIKALOR



W2

# Bridge Clamp ASFA-L (9 mm) W2

ASFA-L Bridge Clamps with 9 mm bandwidth and manufactured with one or two bridges are an ideal solution for hoses with an outer helix.


The geometry and design of the bridges ensure a leaktight fit. These clamps are specially recommended for use on medium-sized and large bore hose mainly used for ventilation or extraction.

* The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.


## Single bridge left


| Size | Part Number | Application Diameter | A | B | C | D | Box Quantity |
|---|---|---|---|---|---|---|---|
| 32-50 | A1PI3250W2L | 32-46 | 10 | 12 | 3,0 | 5 | 100 |
| 40-60 | A1PI4060W2L | 40-56 | 10 | 12 | 3,1 | 5 | 100 |
| 50-70 | A1PI5070W2L | 50-66 | 10 | 12 | 3,2 | 5 | 100 |
| 60-80 | A1PI6080W2L | 60-76 | 10 | 12 | 3,3 | 5 | 100 |
| 70-90 | A1PI7090W2L | 70-86 | 10 | 12 | 3,4 | 5 | 50 |
| 80-100 | A1PI80100W2L | 80-96 | 10 | 12 | 3,5 | 5 | 50 |
| 90-110 | A1PI90110W2L | 90-106 | 10 | 12 | 3,6 | 5 | 25 |
| 100-120 | A1PI100120W2L | 100-116 | 10 | 12 | 3,7 | 5 | 25 |
| 110-130 | A1PI110130W2L | 110-126 | 10 | 12 | 3,8 | 5 | 25 |
| 120-140 | A1PI120140W2L | 120-136 | 10 | 12 | 3,9 | 5 | 25 |
| 130-150 | A1PI130150W2L | 130-146 | 10 | 12 | 3,10 | 5 | 25 |
| 140-160 | A1PI140160W2L | 140-156 | 10 | 12 | 3,11 | 5 | 25 |

**- The maximum pressure and tightening torque values are the same as those indicated in the ASFA-L (9 mm). -**



| TECHNICAL INFORMATION | |
|---|---|
| MATERIAL | Stainless steel band and housing<br>W2 AISI 430 X6Cr17<br>(DIN 1.4016)<br>Steel screw Qst 36-3<br>(DIN 1.0214) Zinc plated Cr3 |
| CORROSION RESISTANCE | 72 hours salt spray<br>(ASTM B-117) |
| MAX. TIGHTENING SPEED (RPM) | 540 ± 5 |







**Available Through BORSERINI SRL**
Via C. Negri 10-12 - 23030 Chiuro (SO) - Italy | +39 0342 209200 | info@borserini.it | www.borserini.com
Registered Office: Via Parolo 38 - 23100 Sondrio (SO) - Italy