MIKALOR



W2

Bridge Clamp ASFA-L (9 mm) W2

ASFA-L Bridge Clamps with 9 mm bandwidth and manufactured with one or two bridges are an ideal solution for hoses with an outer helix.


The geometry and design of the bridges ensure a leaktight fit. These clamps are specially recommended for use on medium-sized and large bore hose mainly used for ventilation or extraction.

* The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.


Double bridge left


Size	Part Number	Application Diameter	A	B	C	D	Box Quantity
32-50	A2PI3250W2L	32-43	10	12	3,0	5	100
40-60	A2PI4060W2L	40-53	10	12	3,1	5	100
50-70	A2PI5070W2L	50-63	10	12	3,2	5	100
60-80	A2PI6080W2L	60-73	10	12	3,3	5	100
70-90	A2PI7090W2L	70-83	10	12	3,4	5	50
80-100	A2PI80100W2L	80-93	10	12	3,5	5	50
90-110	A2PI90110W2L	90-103	10	12	3,6	5	25
100-120	A2PI100120W2L	100-113	10	12	3,7	5	25
110-130	A2PI110130W2L	110-123	10	12	3,8	5	25
120-140	A2PI120140W2L	120-133	10	12	3,9	5	25
130-150	A2PI130150W2L	130-143	10	12	3,10	5	25
140-160	A2PI140160W2L	140-153	10	12	3,11	5	25

- The maximum pressure and tightening torque values are the same as those indicated in the ASFA-L (9 mm). -



TECHNICAL INFORMATION	
MATERIAL	Stainless steel band and housing W2 AISI 430 X6Cr17 (DIN 1.4016) Steel screw Qst 36-3 (DIN 1.0214) Zinc plated Cr3
CORROSION RESISTANCE	72 hours salt spray (ASTM B-117)
MAX. TIGHTENING SPEED (RPM)	540 ± 5





Available Through BORSERINI SRL
Via C. Negri 10-12 - 23030 Chiuro (SO) - Italy | +39 0342 209200 | info@borserini.it | www.borserini.com
Registered Office: Via Parolo 38 - 23100 Sondrio (SO) - Italy