MIKALOR



W4

Bridge Clamp ASFA-L (9 mm) W4

ASFA-L Bridge Clamps with 9 mm bandwidth and manufactured with one or two bridges are an ideal solution for hoses with an outer helix.


The geometry and design of the bridges ensure a leaktight fit. These clamps are specially recommended for use on medium-sized and large bore hose mainly used for ventilation or extraction.

* The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.


Single bridge right


Size	Part Number	Application Diameter	A	B	C	D	Box Quantity
32-50	A1PD3250W4L	32-46	10	12	3,0	5	100
40-60	A1PD4060W4L	40-56	10	12	3,1	5	100
50-70	A1PD5070W4L	50-66	10	12	3,2	5	100
60-80	A1PD6080W4L	60-76	10	12	3,3	5	100
70-90	A1PD7090W4L	70-86	10	12	3,4	5	50
80-100	A1PD80100W4L	80-96	10	12	3,5	5	50
90-110	A1PD90110W4L	90-106	10	12	3,6	5	25
100-120	A1PD100120W4L	100-116	10	12	3,7	5	25
110-130	A1PD110130W4L	110-126	10	12	3,8	5	25
120-140	A1PD120140W4L	120-136	10	12	3,9	5	25
130-150	A1PD130150W4L	130-146	10	12	3,10	5	25
140-160	A1PD140160W4L	140-156	10	12	3,11	5	25

- The maximum pressure and tightening torque values are the same as those indicated in the ASFA-L (9 mm). -



TECHNICAL INFORMATION	
MATERIAL	Stainless steel band and housing W4 AISI 304 X5Cr Ni 18/10 (DIN 1.4301) Stainless steel screw W4 AISI 304
CORROSION RESISTANCE	400 hours salt spray (ASTM B-117)
MAX. TIGHTENING SPEED (RPM)	540 ± 5





Available Through BORSERINI SRL
Via C. Negri 10-12 - 23030 Chiuro (SO) - Italy | +39 0342 209200 | info@borserini.it | www.borserini.com
Registered Office: Via Parolo 38 - 23100 Sondrio (SO) - Italy