MIKALOR



W5

Bridge Clamp ASFA-L (9 mm) W5

ASFA-L Bridge Clamps with 9 mm bandwidth and manufactured with one or two bridges are an ideal solution for hoses with an outer helix.


The geometry and design of the bridges ensure a leaktight fit. These clamps are specially recommended for use on medium-sized and large bore hose mainly used for ventilation or extraction.

* The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.


Double bridge right


Size	Part Number	Application Diameter	A	B	C	D	Box Quantity
32-50	A2PD3250W5L	32-43	10	12	3,0	5	100
40-60	A2PD4060W5L	40-53	10	12	3,1	5	100
50-70	A2PD5070W5L	50-63	10	12	3,2	5	100
60-80	A2PD6080W5L	60-73	10	12	3,3	5	100
70-90	A2PD7090W5L	70-83	10	12	3,4	5	50
80-100	A2PD80100W5L	80-93	10	12	3,5	5	50
90-110	A2PD90110W5L	90-103	10	12	3,6	5	25
100-120	A2PD100120W5L	100-113	10	12	3,7	5	25
110-130	A2PD110130W5L	110-123	10	12	3,8	5	25
120-140	A2PD120140W5L	120-133	10	12	3,9	5	25
130-150	A2PD130150W5L	130-143	10	12	3,10	5	25
140-160	A2PD140160W5L	140-153	10	12	3,11	5	25

- The maximum pressure and tightening torque values are the same as those indicated in the ASFA-L (9 mm). -



TECHNICAL INFORMATION	
MATERIAL	Stainless steel band and housing W5 AISI 316 X5Cr Ni Mo (DIN 1.4401) Stainless steel screw W5 AISI 316 Cu
CORROSION RESISTANCE	1.000 hours salt spray (ASTM B-117)
MAX. TIGHTENING SPEED (RPM)	540 ± 5





Available Through BORSERINI SRL
Via C. Negri 10-12 - 23030 Chiuro (SO) - Italy | +39 0342 209200 | info@borserini.it | www.borserini.com
Registered Office: Via Parolo 38 - 23100 Sondrio (SO) - Italy