MIKALOR



W2

Bridge Clamp ASFA-L (9 mm) W2

ASFA-L Bridge Clamps with 9 mm bandwidth and manufactured with one or two bridges are an ideal solution for hoses with an outer helix.


The geometry and design of the bridges ensure a leaktight fit. These clamps are specially recommended for use on medium-sized and large bore hose mainly used for ventilation or extraction.

* The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.


Single bridge left


Size	Part Number	Application Diameter	A	B	C	D	Box Quantity
32-50	A1PI3250W2S	32-46	10	16	3,0	7	100
40-60	A1PI4060W2S	40-56	10	16	3,0	7	100
50-70	A1PI5070W2S	50-66	10	16	3,0	7	100
60-80	A1PI6080W2S	60-76	10	16	3,0	7	100
70-90	A1PI7090W2S	70-86	10	16	3,0	7	50
80-100	A1PI80100W2S	80-96	10	16	3,0	7	50
90-110	A1PI90110W2S	90-106	10	16	3,0	7	25
100-120	A1PI100120W2S	100-116	10	16	3,0	7	25
110-130	A1PI110130W2S	110-126	10	16	3,0	7	25
120-140	A1PI120140W2S	120-136	10	16	3,0	7	25
130-150	A1PI130150W2S	130-146	10	16	3,0	7	25
140-160	A1PI140160W2S	140-156	10	16	3,0	7	25
150-170	A1PI150170W2S	150-166	10	16	3,0	7	25
160-180	A1PI160180W2S	160-176	10	16	3,0	7	25
170-190	A1PI170190W2S	170-186	10	16	3,0	7	10
180-200	A1PI180200W2S	180-196	10	16	3,0	7	10
190-210	A1PI190210W2S	190-206	10	16	3,0	7	10
200-220	A1PI200220W2S	200-216	10	16	3,0	7	10
210-230	A1PI210230W2S	210-226	10	16	3,0	7	10
220-240	A1PI220240W2S	220-236	10	16	3,0	7	10

- The maximum pressure and tightening torque values are the same as those indicated in the ASFA-S (12 mm). -



TECHNICAL INFORMATION	
MATERIAL	Stainless steel band and housing W2 AISI 430 X6Cr17 (DIN 1.4016) Steel screw Qst 36-3 (DIN 1.0214) Zinc plated Cr3
CORROSION RESISTANCE	72 hours salt spray (ASTM B-117)
MAX. TIGHTENING SPEED (RPM)	540 ± 5





Available Through BORSERINI SRL
Via C. Negri 10-12 - 23030 Chiuro (SO) - Italy | +39 0342 209200 | info@borserini.it | www.borserini.com
Registered Office: Via Parolo 38 - 23100 Sondrio (SO) - Italy