MIKALOR



W2

Bridge Clamp ASFA-S (12 mm) W2

ASFA-S Bridge Clamps with 12 mm bandwidth and manufactured with one or two bridges are an ideal solution for hoses with an outer helix.


The geometry and design of the bridges ensure a leaktight fit. These clamps are specially recommended for use on medium-sized and large bore hose mainly used for ventilation or extraction.

* The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.


Single bridge right


Size	Part Number	Application Diameter	A	B	C	D	Box Quantity
32-50	A1PD3250W2S	32-46	10	16	3,0	7	100
40-60	A1PD4060W2S	40-56	10	16	3,0	7	100
50-70	A1PD5070W2S	50-66	10	16	3,0	7	100
60-80	A1PD6080W2S	60-76	10	16	3,0	7	100
70-90	A1PD7090W2S	70-86	10	16	3,0	7	50
80-100	A1PD80100W2S	80-96	10	16	3,0	7	50
90-110	A1PD90110W2S	90-106	10	16	3,0	7	25
100-120	A1PD100120W2S	100-116	10	16	3,0	7	25
110-130	A1PD110130W2S	110-126	10	16	3,0	7	25
120-140	A1PD120140W2S	120-136	10	16	3,0	7	25
130-150	A1PD130150W2S	130-146	10	16	3,0	7	25
140-160	A1PD140160W2S	140-156	10	16	3,0	7	25
150-170	A1PD150170W2S	150-166	10	16	3,0	7	25
160-180	A1PD160180W2S	160-176	10	16	3,0	7	25
170-190	A1PD170190W2S	170-186	10	16	3,0	7	10
180-200	A1PD180200W2S	180-196	10	16	3,0	7	10
190-210	A1PD190210W2S	190-206	10	16	3,0	7	10
200-220	A1PD200220W2S	200-216	10	16	3,0	7	10
210-230	A1PD210230W2S	210-226	10	16	3,0	7	10
220-240	A1PD220240W2S	220-236	10	16	3,0	7	10

- The maximum pressure and tightening torque values are the same as those indicated in the ASFA-S (12 mm). -



TECHNICAL INFORMATION	
MATERIAL	Stainless steel band and housing W2 AISI 430 X6Cr17 (DIN 1.4016) Steel screw Qst 36-3 (DIN 1.0214) Zinc plated Cr3
CORROSION RESISTANCE	72 hours salt spray (ASTM B-117)
MAX. TIGHTENING SPEED (RPM)	540 ± 5





Available Through BORSERINI SRL
Via C. Negri 10-12 - 23030 Chiuro (SO) - Italy | +39 0342 209200 | info@borserini.it | www.borserini.com
Registered Office: Via Parolo 38 - 23100 Sondrio (SO) - Italy