MIKALOR



W2

Bridge Clamp ASFA-S (12 mm) W2

ASFA-S Bridge Clamps with 12 mm bandwidth and manufactured with one or two bridges are an ideal solution for hoses with an outer helix.


The geometry and design of the bridges ensure a leaktight fit. These clamps are specially recommended for use on medium-sized and large bore hose mainly used for ventilation or extraction.

* The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.


Double bridge right


Size	Part Number	Application Diameter	A	B	C	D	Box Quantity
32-50	A2PD3250W2S	32-43	10	16	3,0	7	100
40-60	A2PD4060W2S	40-53	10	16	3,0	7	100
50-70	A2PD5070W2S	50-63	10	16	3,0	7	100
60-80	A2PD6080W2S	60-73	10	16	3,0	7	100
70-90	A2PD7090W2S	70-83	10	16	3,0	7	50
80-100	A2PD80100W2S	80-93	10	16	3,0	7	50
90-110	A2PD90110W2S	90-103	10	16	3,0	7	25
100-120	A2PD100120W2S	100-113	10	16	3,0	7	25
110-130	A2PD110130W2S	110-123	10	16	3,0	7	25
120-140	A2PD120140W2S	120-133	10	16	3,0	7	25
130-150	A2PD130150W2S	130-143	10	16	3,0	7	25
140-160	A2PD140160W2S	140-153	10	16	3,0	7	25
150-170	A2PD150170W2S	150-163	10	16	3,0	7	25
160-180	A2PD160180W2S	160-173	10	16	3,0	7	25
170-190	A2PD170190W2S	170-183	10	16	3,0	7	10
180-200	A2PD180200W2S	180-193	10	16	3,0	7	10
190-210	A2PD190210W2S	190-203	10	16	3,0	7	10
200-220	A2PD200220W2S	200-213	10	16	3,0	7	10
210-230	A2PD210230W2S	210-223	10	16	3,0	7	10
220-240	APD220240W2S	220-233	10	16	3,0	7	10

- The maximum pressure and tightening torque values are the same as those indicated in the ASFA-S (12 mm). -



TECHNICAL INFORMATION	
MATERIAL	Stainless steel band and housing W2 AISI 430 X6Cr17 (DIN 1.4016) Steel screw Qst 36-3 (DIN 1.0214) Zinc plated Cr3
CORROSION RESISTANCE	72 hours salt spray (ASTM B-117)
MAX. TIGHTENING SPEED (RPM)	540 ± 5





Available Through BORSERINI SRL
Via C. Negri 10-12 - 23030 Chiuro (SO) - Italy | +39 0342 209200 | info@borserini.it | www.borserini.com
Registered Office: Via Parolo 38 - 23100 Sondrio (SO) - Italy