MIKALOR



W3

Bridge Clamp ASFA-S (12 mm) W3

ASFA-S Bridge Clamps with 12 mm bandwidth and manufactured with one or two bridges are an ideal solution for hoses with an outer helix.


The geometry and design of the bridges ensure a leaktight fit. These clamps are specially recommended for use on medium-sized and large bore hose mainly used for ventilation or extraction.

* The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.


Double bridge right


Size	Part Number	Application Diameter	A	B	C	D	Box Quantity
32-50	A2PD3250W3S	32-46	10	16	3,0	7	100
40-60	A2PD4060W3S	40-56	10	16	3,0	7	100
50-70	A2PD5070W3S	50-66	10	16	3,0	7	100
60-80	A2PD6080W3S	60-76	10	16	3,0	7	100
70-90	A2PD7090W3S	70-86	10	16	3,0	7	50
80-100	A2PD80100W3S	80-96	10	16	3,0	7	50
90-110	A2PD90110W3S	90-106	10	16	3,0	7	25
100-120	A2PD100120W3S	100-116	10	16	3,0	7	25
110-130	A2PD110130W3S	110-126	10	16	3,0	7	25
120-140	A2PD120140W3S	120-136	10	16	3,0	7	25
130-150	A2PD130150W3S	130-146	10	16	3,0	7	25
140-160	A2PD140160W3S	140-156	10	16	3,0	7	25
150-170	A2PD150170W3S	150-166	10	16	3,0	7	25
160-180	A2PD160180W3S	160-176	10	16	3,0	7	25
170-190	A2PD170190W3S	170-186	10	16	3,0	7	10
180-200	A2PD180200W3S	180-196	10	16	3,0	7	10
190-210	A2PD190210W3S	190-206	10	16	3,0	7	10
200-220	A2PD200220W3S	200-216	10	16	3,0	7	10
210-230	A2PD210230W3S	210-226	10	16	3,0	7	10
220-240	APD220240W3S	220-236	10	16	3,0	7	10

- The maximum pressure and tightening torque values are the same as those indicated in the ASFA-S (12 mm). -



TECHNICAL INFORMATION	
MATERIAL	Stainless steel band and housing W3 AISI 430 X6Cr17 (DIN 1.4016) Stainless steel screw W4 AISI 304 Cu
CORROSION RESISTANCE	200 hours salt spray (ASTM B-117)
MAX. TIGHTENING SPEED (RPM)	540 ± 5





Available Through BORSERINI SRL
Via C. Negri 10-12 - 23030 Chiuro (SO) - Italy | +39 0342 209200 | info@borserini.it | www.borserini.com
Registered Office: Via Parolo 38 - 23100 Sondrio (SO) - Italy