MIKALOR



W4

Bridge Clamp ASFA-S (12 mm) W4

ASFA-S Bridge Clamps with 12 mm bandwidth and manufactured with one or two bridges are an ideal solution for hoses with an outer helix.


The geometry and design of the bridges ensure a leaktight fit. These clamps are specially recommended for use on medium-sized and large bore hose mainly used for ventilation or extraction.

* The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.


Single bridge left


Size	Part Number	Application Diameter	A	B	C	D	Box Quantity
32-50	A1PI3250W4S	32-43	10	16	3,0	7	100
40-60	A1PI4060W4S	40-53	10	16	3,0	7	100
50-70	A1PI5070W4S	50-63	10	16	3,0	7	100
60-80	A1PI6080W4S	60-73	10	16	3,0	7	100
70-90	A1PI7090W4S	70-83	10	16	3,0	7	50
80-100	A1PI80100W4S	80-93	10	16	3,0	7	50
90-110	A1PI90110W4S	90-103	10	16	3,0	7	25
100-120	A1PI100120W4S	100-113	10	16	3,0	7	25
110-130	A1PI110130W4S	110-123	10	16	3,0	7	25
120-140	A1PI120140W4S	120-133	10	16	3,0	7	25
130-150	A1PI130150W4S	130-143	10	16	3,0	7	25
140-160	A1PI140160W4S	140-153	10	16	3,0	7	25
150-170	A1PI150170W4S	150-163	10	16	3,0	7	25
160-180	A1PI160180W4S	160-173	10	16	3,0	7	25
170-190	A1PI170190W4S	170-183	10	16	3,0	7	10
180-200	A1PI180200W4S	180-193	10	16	3,0	7	10
190-210	A1PI190210W4S	190-203	10	16	3,0	7	10
200-220	A1PI200220W4S	200-213	10	16	3,0	7	10
210-230	A1PI210230W4S	210-223	10	16	3,0	7	10
220-240	A1PI220240W4S	220-233	10	16	3,0	7	10

- The maximum pressure and tightening torque values are the same as those indicated in the ASFA-S (12 mm). -



TECHNICAL INFORMATION	
MATERIAL	Stainless steel band and housing W4 AISI 304 X5Cr Ni 18/10 (DIN 1.4301) Stainless steel screw W4 AISI 304
CORROSION RESISTANCE	400 hours salt spray (ASTM B-117)
MAX. TIGHTENING SPEED (RPM)	540 ± 5





Available Through BORSERINI SRL
Via C. Negri 10-12 - 23030 Chiuro (SO) - Italy | +39 0342 209200 | info@borserini.it | www.borserini.com
Registered Office: Via Parolo 38 - 23100 Sondrio (SO) - Italy