MIKALOR



W5

Bridge Clamp ASFA-S (12 mm) W5

ASFA-S Bridge Clamps with 12 mm bandwidth and manufactured with one or two bridges are an ideal solution for hoses with an outer helix.


The geometry and design of the bridges ensure a leaktight fit. These clamps are specially recommended for use on medium-sized and large bore hose mainly used for ventilation or extraction.

* The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.


Single bridge right


Size	Part Number	Application Diameter	A	B	C	D	Box Quantity
32-50	A1PD3250W5S	32-46	10	16	3,0	7	100
40-60	A1PD4060W5S	40-56	10	16	3,0	7	100
50-70	A1PD5070W5S	50-66	10	16	3,0	7	100
60-80	A1PD6080W5S	60-76	10	16	3,0	7	100
70-90	A1PD7090W5S	70-86	10	16	3,0	7	50
80-100	A1PD80100W5S	80-96	10	16	3,0	7	50
90-110	A1PD90110W5S	90-106	10	16	3,0	7	25
100-120	A1PD100120W5S	100-116	10	16	3,0	7	25
110-130	A1PD110130W5S	110-126	10	16	3,0	7	25
120-140	A1PD120140W5S	120-136	10	16	3,0	7	25
130-150	A1PD130150W5S	130-146	10	16	3,0	7	25
140-160	A1PD140160W5S	140-156	10	16	3,0	7	25
150-170	A1PD150170W5S	150-166	10	16	3,0	7	25
160-180	A1PD160180W5S	160-176	10	16	3,0	7	25
170-190	A1PD170190W5S	170-186	10	16	3,0	7	10
180-200	A1PD180200W5S	180-196	10	16	3,0	7	10
190-210	A1PD190210W5S	190-206	10	16	3,0	7	10
200-220	A1PD200220W5S	200-216	10	16	3,0	7	10
210-230	A1PD210230W5S	210-226	10	16	3,0	7	10
220-240	A1PD220240W5S	220-236	10	16	3,0	7	10

- The maximum pressure and tightening torque values are the same as those indicated in the ASFA-S (12 mm). -



TECHNICAL INFORMATION	
MATERIAL	Stainless steel band and housing W5 AISI 316 X5Cr Ni Mo (DIN 1.4401) Stainless steel screw W5 AISI 316 Cu
CORROSION RESISTANCE	1.000 hours salt spray (ASTM B-117)
MAX. TIGHTENING SPEED (RPM)	540 ± 5





Available Through BORSERINI SRL
Via C. Negri 10-12 - 23030 Chiuro (SO) - Italy | +39 0342 209200 | info@borserini.it | www.borserini.com
Registered Office: Via Parolo 38 - 23100 Sondrio (SO) - Italy