KA-GH PU MHR

Applications dental technology, cable protection, medical devices

Structure Polyether-Polyurethane, grey / light grey (similar RAL 7035), opaque, plastic spiral / rigid PVC

Temperature -10°C up to 60°C

Properties light weight, excellent flexibility, smooth outside, very smooth inside, hydrolysis & microbe resistant, rot proof, weather proof



Technical data

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)
8	12,00	2,00	10	0,03	0,30	0,09300
10	14,00	2,00	12	0,09	0,29	0,12400
11	15,00	2,00	13	0,09	0,29	0,12500
13	17,00	2,00	13	0,09	0,28	0,16500
15	19,00	2,00	13	0,10	0,27	0,13800
16	20,00	2,00	20	0,12	0,26	0,14700
17	21,00	2,00	21	0,13	0,25	0,15400
20	25,00	2,00	21	0,14	0,23	0,18300
25	30,00	2,50	23	0,19	0,20	0,22900

Original technical data by OCONO - VACUFLEX

Available Through BORSERINI SRL
Via C. Negri 10-12 - 23030 Chiuro (SO) - Italy | +39 0342 209200 | info@borserini.it | www.borserini.com
Registered Office: Via Parolo 38 - 23100 Sondrio (SO) - Italy