KA-GH PVC

Applications dental technology, medical devices, cable protection

Structure PVC, grey / light grey (similar RAL 7035), opaque, plastic spiral / rigid PVC

Temperature -5°C up to 60°C

Properties light weight, excellent flexibility, smooth outside, very smooth inside, hydrolysis & microbe resistant, weather proof, rot proof



Technical data

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Vacuum Max. (bar)	Weight (kg/m)
8	12,00	2,00	10	0,25	0,06000
10	14,00	2,00	12	0,24	0,11800
11	15,00	2,00	13	0,24	0,12300
12	16,00	2,00	13	0,23	0,08500
13	17,00	2,00	13	0,23	0,13200
15	19,00	2,00	13	0,22	0,10600
16	20,00	2,00	20	0,21	0,14000
17	21,00	2,00	21	0,21	0,15000
19	24,00	2,00	21	0,20	0,17000
20	25,00	2,50	21	0,18	0,17900
22	27,00	2,50	23	0,17	0,19500
25	30,00	2,50	23	0,15	0,32900

Original technical data by OCONO - VACUFLEX

Available Through BORSERINI SRL
Via C. Negri 10-12 - 23030 Chiuro (SO) - Italy | +39 0342 209200 | info@borserini.it | www.borserini.com
Registered Office: Via Parolo 38 - 23100 Sondrio (SO) - Italy