KD-STRETCH PVC



Applications vacuum cleaner, cleaning, extraction systems, industrial vacuum cleaners, drying

Structure soft PVC, black / jet black (similar RAL 9005), opaque, steel wire / spring steel wire / coated / PVC

Temperature -10°C up to 70°C

Properties excellent flexibility, good abrasion resistance, good flexibility restoring force after compression or bending, good compression ratio, very good resilience when pressed or twisted, hydrolysis & microbe resistant, weather proof, rot proof, good tensile strength, ultimate elongation

Technical data

Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius (mm)	Vacuum Max. (bar)	Weight (kg/m)
25	30,00	25	0,55	0,43000
30	35,00	30	0,50	0,51000
32	37,00	32	0,50	0,54000
38	43,00	38	0,45	0,65000
40	45,00	40	0,45	0,91000
44	49,00	55	0,45	1,39000
51	56,00	51	0,40	1,16000

Original technical data by OCONO - VACUFLEX

Available Through BORSERINI SRL
Via C. Negri 10-12 - 23030 Chiuro (SO) - Italy | +39 0342 209200 | info@borserini.it | www.borserini.com
Registered Office: Via Parolo 38 - 23100 Sondrio (SO) - Italy