MIKALOR



W1

“Normal” Mini Clip W1


The use of malleable mild steel in the manufacture of the “Normal” mini clip means that when tightened, the clip adapts perfectly to the hose, clamping firmly but gently.

This clip is recommended for use with gaseous fluids at low pressure and on small-boreor thin-walled hoses.


“Normal” also has many applications in the automotive industry.

*** The maximum pressure may vary depending on the type of hose and coupling used.**

							Maximum values			
Ø Application mm	Part Number	r	e	a	b ±1	s	Pressure (Bar)	Torque (Nm)	Box Quantity	Outer Box Quantity
6	03010510	M3	5	8,4	5,0	0,5	15,0	0,4	100	1.600
8	03010528	M3	5	9,0	6,5	0,5	14,0	0,4	100	1.600
9	03010536	M4	6	10,0	7,0	0,5	15,0	1,0	100	1.600
9,5-10	03010544	M4	6	10,0	7,0	0,5	14,0	1,0	100	1.600
10-11	03010552	M4	6	10,0	7,0	0,5	13,0	1,0	100	1.600
12-13	03010560	M4	6	10,0	7,0	0,5	12,5	1,0	100	1.600
13-14	03010579	M4	6	10,0	7,0	0,5	12,5	1,0	100	1.600
14-15	03010587	M4	6	10,0	7,0	0,5	12,0	1,0	100	1.600
15-17	03010595	M4	6	10,0	7,0	0,5	12,0	1,0	100	1.600
16-18	03010608	M4	6	10,0	7,0	0,5	11,5	1,0	100	1.600
18-20	03010616	M4	6	10,0	7,0	0,5	10,5	1,0	100	1.600
19-21	03010624	M4	6	10,0	7,0	0,5	10,5	1,0	100	800
20-22	03010632	M4	6	10,0	7,0	0,5	10,5	1,0	100	800
22-25	03010640	M4	6	10,0	7,0	0,5	9,5	1,0	100	800
23-26	03010659	M4	6	10,0	7,0	0,5	9,0	1,0	100	800
25-28	03010667	M4	6	10,0	7,0	0,5	8,5	1,0	100	800
26-29	03010675	M4	6	10,0	7,0	0,5	8,5	1,0	100	800
29-32	03010683	M4	6	10,0	7,0	0,5	8,0	1,0	100	800



TECHNICAL INFORMATION	
MATERIAL	Steel W1 St 02Z (DIN 1.0226) Grade 5.8 steel screw Grade 5 steel nut
FINISH	Zinc plated Cr3
CORROSION RESISTANCE	144 hours salt spray (ASTM B-117)



Available Through BORSERINI SRL
Via C. Negri 10-12 - 23030 Chiuro (SO) - Italy | +39 0342 209200 | info@borserini.it | www.borserini.com
Registered Office: Via Parolo 38 - 23100 Sondrio (SO) - Italy