


The PFPU-20 is a 20 gpm portable contaminant removal system for use in both above- and below-ground fuel storage tanks. It is designed specifically to remove water and othe heavy contaminants common to stored diesel fuel. Options include: bag filter for sludge removal, high-efficiency fuel filter, three-phase fuel coalescer with a 99.5% single-pass water removal efficiency, and power upgrades.



Product Details

Product Line Model Dimensions Weight Portable Fuel Polishing Unit PFPU-20 50" H x 22" W x 31" D approximately 200 lbs.

Pump and Motor

Standard Power Power Upgrade Motor Horse Power **Motor Operation** Max. Operating Pressure Pump Horse Power **Pump Operation** Nominal Flow

Fuel Purifier

Model Number **Nominal Flow** Water Drain Port **Free Water Removal Contaminant Removal**

115VAC, 50 or 60 Hz, Single Phase
220VAC, 50 or 60 Hz, Single Phase
1/3 hp
Self-Priming
78 psi
1/3 hp
Portable
20 gpm

FP 1000
20 gpm
1/2″
up to 99.8%
up to 95%

0000	
Foot Suction Hose	20' x 3/4"
Foot Pressure Hose	12' x 3/4"
Manual Shut-Off Nozzle	3/4″

Optional Filtration

Three-Phase Coalescer	5 micron
Emulsified Water Removal	99.5% Single-Pass Water Removal
High-Efficiency Fuel Filter	3 micron

Additional Features

- 90-Degree Swivel Couplings
- 25' Power Cord
- Removable Drip Pan
- One Year Manufacturer's Warranty on pump
- Optional: Bag Filter, High-Efficiency Fuel Filter, Three-Phase Fuel Coalescer

