
MIKALOR



W5

Supra 2-bolt heavy-duty clamp W5

The SUPRA 2-bolt heavy-duty clamp is an ideal solution for applications where increased performance and improved distribution of radial forces around the circumference of the band are required.


In order to ensure maximum clamping force, our bolts are manufactured in-house by Mikalor with an exclusively designed outer hexagonal head which guarantees the highest clamping force on the market.

The bevelled band edges avoid damage to the hose, making Supra safe and reliable to use.

This 2-bolt version of the Supra clamp is recommended for applications with an outer diameter (OD) over 270mm for use in sectors such as Oil and Gas, Marine, Agriculture, Foodstuffs, Hydraulics and Chemicals amongst others.

Ø D Application mm	Part Number	Ø D +0.3 -0.2	A ±0.3	S ±0.3	B ±0.5	E ±0.2	Tightening Torque (Nm)	Box Quantity	Outer Box Quantity
270-280	03190001	280	28	1,2	31	15	30	5	5
280-290	03190003	290	28	1,2	31	15	30	5	5
285-295	03190005	295	28	1,2	31	15	30	5	5
315-325	03190007	325	28	1,2	31	15	30	5	5
345-355	03190009	355	28	1,2	31	15	30	5	5
370-385	03190011	385	28	1,2	31	15	30	5	5
395-410	03190013	410	28	1,2	31	15	30	5	5
420-435	03190015	435	28	1,2	31	15	30	5	5
445-460	03190017	460	28	1,2	31	15	30	5	5
470-485	03190019	485	28	1,2	31	15	30	5	5
495-510	03190021	510	28	1,2	31	15	30	5	5
520-535	03190023	535	28	1,2	31	15	30	5	5
545-560	03190025	560	28	1,2	31	15	30	5	5
570-585	03190027	585	28	1,2	31	15	30	5	5
595-610	03190029	610	28	1,2	31	15	30	5	5
620-635	03190031	635	28	1,2	31	15	30	5	5
650-665	03190033	665	28	1,2	31	15	30	5	5
680-695	03190035	695	28	1,2	31	15	30	5	5
715-730	03190037	730	28	1,2	31	15	30	5	5
740-755	03190039	755	28	1,2	31	15	30	5	5
765-780	03190041	780	28	1,2	31	15	30	5	5
790-805	03190043	805	28	1,2	31	15	30	5	5
820-835	03190045	835	28	1,2	31	15	30	5	5

	TECHNICAL INFORMATION	
	MATERIAL	Stainless steel band and bridge W5 AISI 316 Steel nuts and screws
	CORROSION RESISTANCE	1.000 hours salt spray (ASTM B-117)
	MAX. TIGHTENING SPEED (RPM)	540 ± 5



Available Through BORSERINI SRL
Via C. Negri 10-12 - 23030 Chiuro (SO) - Italy | +39 0342 209200 | info@borserini.it | www.borserini.com
Registered Office: Via Parolo 38 - 23100 Sondrio (SO) - Italy