



NOTE:  
NOTES:

1. TUTTE LE DIMENSIONI SONO SOLO DI RIFERIMENTO  
ALL DIMENSIONS FOR REFERENCE ONLY
2. MATERIALE: NYLON NERO 6 (PA6GF30)  
MATERIAL: BLACK NYLON 6, GLASS FILL
3. HARDWARE DI MONTAGGIO E COLLARE DI SERRAGGIO  
(P/N 21-1012113) INCLUSI  
MOUNTING HARDWARE AND CLAMP  
(P/N 21-1012113) INCLUDED
4. PORTATA NOMINALE: DA 15 A 75 C.F.M. [ DA 0.42 A 2.12 M<sup>3</sup>/MIN]  
RATED RANGE: 15 TO 75 C.F.M. [0.42 TO 2.12 M<sup>3</sup>/MIN]
5. APPLICAZIONE: ADATTO PER MANICOTTI 2.00" [50.8MM]  
DEVE ESSERE MONTATO ORIZZONTALMENTE  
APPLICATION: FITS 2.00" [50.8MM] AIR INTAKE  
MUST BE MOUNTED HORIZONTALLY
6. TEMPERATURA DI ESERCIZIO:  
DA -30°C (-22°F) A +110°C (+230°F)  
RATED AMBIENT TEMPERATURE RANGE:  
-30°C (-22°F) TO +110°C (+230°F)
7. DIMENSIONI: POLLICI [MILLIMETERI]  
DIMENSIONS: INCHES [MILLIMETERS]

Rev. no.	CHANGE	DATE	SIGNATURE	NA-ECR-No.
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-
<b>BORSERINI SRL</b>				
MATERIAL	-	Rev No	SHEET SIZE	MASS: FINAL WEIGHT IN KG
SEMI - PRODUCT	-	00	A0	SCALE: 2:1
STANDARD	ISO 2768 - c	DATE DRAWN	17/05/12	No. of ASSEMBLY
DRAWN BY	M.COMETTI	APPROVED BY	M.BORSERINI	ITEM No.
CHECKED BY	M.BORSERINI	DATE	28/04/17	GROUP:
TECHNOLOGIST	-	DATE	28/04/17	PART NO.:
DESCRIPTION:			PART No.:	
TURBO III POLYMER 15-2 BN			PCF1010246	
PROJECTION:				SHEET:
				1 of 1