



**NOTE:
NOTES:**

1. TUTTE LE DIMENSIONI SONO SOLO DI RIFERIMENTO
ALL DIMENSIONS FOR REFERENCE ONLY
2. MATERIALE: NYLON NERO 6 (PA6GF30)
MATERIAL: BLACK NYLON 6, GLASS FILL
3. ISTRUZIONI DI MONTAGGIO E COLLARE DI SERRAGGIO
(P/N 21-1200108) INCLUSI
MOUNTING INSTRUCTIONS AND CLAMP
(P/N 21-1200108) INCLUDED
4. PORTATA NOMINALE: DA 500 A 1100 C.F.M. [DA 14.2 A 31.1 M³/MIN]
RATED RANGE: 500 TO 1100 C.F.M. [14.2 TO 31.1 M³/MIN]
5. TEMPERATURA DI ESERCIZIO:
DA -30°C (-22°F) A +110°C (+230°F)
RATED AMBIENT TEMPERATURE RANGE:
-30°C (-22°F) TO +110°C (+230°F)
6. DIMENSIONI: POLLICI [MILLIMETERI]
DIMENSIONS: INCHES [MILLIMETERS]

Rev. no.	CHANGE	DATE	SIGNATURE	NA-ECR-No.	BORSERINI SRL
-	-	-	-	-	
-	-	-	-	-	
-	-	-	-	-	
MATERIAL	-	Rev No	SHEET SIZE	MASS: FINAL WEIGHT IN KG	SCALE: 1:1
SEMI - PRODUCT	-	00	A0		
STANDARD	ISO 2768 - c			No. of ASSEMBLY	ITEM No.
DRAWN BY	M.COMETTI	DATE DRAWN	24/07/14		
CHECKED BY	M.BORSERINI	APPROVED BY	M.BORSERINI		
TECHNOLOGIST	-	DATE	27/04/17	GROUP:	PART No.:
DESCRIPTION:				PART No.:	PROJECTION:
TURBO III 500-6"				PCF1010227	
				SHEET:	1 of 1