



**NOTE:
NOTES:**

1. TUTTE LE DIMENSIONI SONO SOLO DI RIFERIMENTO
ALL DIMENSIONS FOR REFERENCE ONLY
2. MATERIALE: NYLON NERO 6 (PA6GF30)
MATERIAL: BLACK NYLON 6, GLASS FILL
3. ISTRUZIONI DI MONTAGGIO E COLLARE DI SERRAGGIO
(P/N 21-1200104) INCLUSI
MOUNTING INSTRUCTIONS AND CLAMP
(P/N 21-1200104) INCLUDED

4. PORTATA NOMINALE: DA 200 A 500 C.F.M. [DA 5.7 A 14.2 M³/MIN]
RATED RANGE: 200 TO 500 C.F.M. [5.7 TO 14.2 M³/MIN]
5. TEMPERATURA DI ESERCIZIO:
DA -30°C (-22°F) A +110°C (+230°F)
RATED AMBIENT TEMPERATURE RANGE:
-30°C (-22°F) TO +110°C (+230°F)
6. DIMENSIONI: POLLICI [MILLIMETERI]
DIMENSIONS: INCHES [MILLIMETERS]

Rev. no.	CHANGE	DATE	SIGNATURE	NA-ECR-No.	 BORSERINI SRL	
-	-	-	-	-		
-	-	-	-	-		
-	-	-	-	-		
MATERIAL		Rev No		SHEET SIZE	MASS: FINAL WEIGHT IN KG	SCALE:
SEMI - PRODUCT		00		A0		1:1
STANDARD		ISO 2768 - c		No. of ASSEMBLY		ITEM No.
DRAWN BY	M.COMETTI	DATE DRAWN	24/07/14			
CHECKED BY	M.BORSERINI	APPROVED BY	M.BORSERINI			
TECHNOLOGIST	-	DATE	27/04/17		GROUP:	PART No.:
DESCRIPTION:				PART No.:		PROJECTION:
TURBO III 200-5"				PCF1010228		
						SHEET: 1 of 1