



**NOTE:  
NOTES:**

1. TUTTE LE DIMENSIONI SONO SOLO DI RIFERIMENTO  
ALL DIMENSIONS FOR REFERENCE ONLY
2. MATERIALE: NYLON NERO 6 (PA6GF30)  
MATERIAL: BLACK NYLON 6, GLASS FILL
3. ISTRUZIONI DI MONTAGGIO E COLLARE DI SERRAGGIO  
(P/N 21-1200112) INCLUSI  
MOUNTING INSTRUCTIONS AND CLAMP  
(P/N 21-1200112) INCLUDED
4. PORTATA NOMINALE: DA 500 A 1100 C.F.M. [ DA 14.2 A 31.1 M<sup>3</sup>/MIN]  
RATED RANGE: 500 TO 1100 C.F.M. [14.2 TO 31.1 M<sup>3</sup>/MIN]
5. TEMPERATURA DI ESERCIZIO:  
DA -30°C (-22°F) A +110°C (+230°F)  
RATED AMBIENT TEMPERATURE RANGE:  
-30°C (-22°F) TO +110°C (+230°F)
6. DIMENSIONI: POLLICI [MILLIMETERI]  
DIMENSIONS: INCHES [MILLIMETERS]

Rev. no.	CHANGE	DATE	SIGNATURE	NA-ECR-No.	<b>B</b> BORSERINI SRL
-	-	-	-	-	
-	-	-	-	-	
-	-	-	-	-	
MATERIAL	-	Rev No	SHEET SIZE	MASS: FINAL WEIGHT IN KG	SCALE: 1:1
SEMI - PRODUCT	-	00	A0	No. of ASSEMBLY	ITEM No.
STANDARD	ISO 2768 - c	DATE DRAWN	24/07/14		
DRAWN BY	M.COMETTI	APPROVED BY	M.BORSERINI		
CHECKED BY	M.BORSERINI	DATE	27/04/17	GROUP:	PART No.:
TECHNOLOGIST	-				
DESCRIPTION:				PART No.:	
TURBO III 500-7"				PCF1010226	
				PROJECTION:	
				SHEET: 1 of 1	