



NOTE:
NOTES:

1. TUTTE LE DIMENSIONI SONO SOLO DI RIFERIMENTO
ALL DIMENSIONS FOR REFERENCE ONLY
2. MATERIALE: NYLON NERO 6 (PA6GF30)
MATERIAL: BLACK NYLON 6, GLASS FILL
3. HARDWARE DI MONTAGGIO E COLLARE DI SERRAGGIO
(P/N 21-1200100) INCLUSI
MOUNTING HARDWARE AND CLAMP
(P/N 21-1200100) INCLUDED
4. PORTATA NOMINALE: DA 50 A 250 C.F.M. [DA 1.42 A 7.07 M³/MIN]
RATED RANGE: 50 TO 250 C.F.M. [1.42 TO 7.07 M³/MIN]

5. APPLICAZIONE: ADATTO PER MANICOTTI 3.00" [76MM]
APPLICATION: FITS 3.00" [76MM] AIR INTAKE
6. TEMPERATURA DI ESERCIZIO:
DA -30°C (-22°F) A +110°C (+230°F)
RATED AMBIENT TEMPERATURE RANGE:
-30°C (-22°F) TO +110°C (+230°F)
7. DIMENSIONI: POLLICI [MILLIMETERI]
DIMENSIONS: INCHES [MILLIMETERS]

Rev. no.	CHANGE	DATE	SIGNATURE	NA-ECR-No.	B BORSERINI SRL
-	-	-	-	-	
-	-	-	-	-	
-	-	-	-	-	
MATERIAL	-	Rev No	SHEET SIZE	MASS: FINAL WEIGHT IN KG	SCALE: 1:1
SEMI - PRODUCT	-	00	A0	No. of ASSEMBLY	ITEM No.
STANDARD	ISO 2768 - c	DRAWN BY	DATE DRAWN		
		M.COMETTI	24/07/14		
CHECKED BY	M.BORSERINI	APPROVED BY	M.BORSERINI		
TECHNOLOGIST	-	DATE	27/04/17	GROUP:	PART NO.:
DESCRIPTION:			PART No.:		PROJECTION:
TURBO III 50-3"			PCF1010230		
					SHEET: 1 of 1