VC1 PU MHR

Applications extraction systems, air supply, air extraction, cable protection, medical devices

Structure Polyether-Polyurethane, black / jet black (similar RAL 9005), opaque, plastic spiral / rigid PVC

Temperature -20°C up to 60°C

Properties light weight, corrugated outside, smooth inside, good chemical resistance, good tensile strength, ultimate elongation, good ozone- & UV-resistance, hydrolysis & microbe resistant, rot proof, weather proof

Technical data

Inner Diameter (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)
10	10	2,50	0,85	0,07200
13	13	2,50	0,85	0,09300
20	20	2,50	0,85	0,14400
25	25	2,00	0,55	0,18500
30	30	2,00	0,55	0,22200
32	32	2,00	0,55	0,23600
38	38	1,50	0,50	0,27800
40	40	1,50	0,50	0,29600
45	45	1,50	0,50	0,33000
50	50	1,00	0,45	0,37000

Original technical data by OCONO - VACUFLEX

Available Through BORSERINI SRL
Via C. Negri 10-12 - 23030 Chiuro (SO) - Italy | +39 0342 209200 | info@borserini.it | www.borserini.com
Registered Office: Via Parolo 38 - 23100 Sondrio (SO) - Italy