VC2 PU MHR

Applications cable protection, conveying of abrasive media, conveying technology, granulate conveying, medical devices

Structure Polyether-Polyurethane, black / jet black (similar RAL 9005), opaque, plastic spiral / rigid PVC

Temperature -30°C up to 90°C

Properties good flexibility, good abrasion resistance, corrugated outside, very smooth inside, good ozone- & UV-resistance, hydrolysis & microbe resistant, rot proof, weather proof



Technical data

Inner Diameter (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)
10	10	3,50	0,95	0,06000
13	13	3,50	0,95	0,09500
20	20	3,50	0,95	0,14800
25	25	2,50	0,65	0,18900
30	30	2,50	0,65	0,22600
32	32	2,50	0,65	0,18000
38	38	2,50	0,60	0,26600
40	40	2,50	0,60	0,31000
45	45	2,50	0,60	0,33700
50	50	2,00	0,55	0,37700
60	60	2,00	0,55	0,45200

Original technical data by OCONO - VACUFLEX

Available Through BORSERINI SRL
Via C. Negri 10-12 - 23030 Chiuro (SO) - Italy | +39 0342 209200 | info@borserini.it | www.borserini.com
Registered Office: Via Parolo 38 - 23100 Sondrio (SO) - Italy