VC2 TPR

Applications automotive engineering, vehicle construction, air conditioning & HVAC, steam extraction, air supply

Structure TPR, black / jet black (similar RAL 9005), opaque, plastic spiral / PP

Temperature -40°C up to 100°C

Properties light weight, good flexibility, good chemical resistance, corrugated outside, very smooth inside, good ozone- & UV-resistance, hydrolysis & microbe resistant, rot proof, weather proof



Technical data

Inner Diameter (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)
8	8	2,50	0,75	0,04500
10	10	2,50	0,75	0,05500
12	12	2,50	0,75	0,06900
14	14	2,50	0,75	0,07400
16	16	2,50	0,75	0,08600
18	18	2,50	0,75	0,09800
20	20	2,50	0,75	0,11000
22	22	2,50	0,75	0,12500
25	25	2,00	0,55	0,14200
26	26	2,00	0,55	0,15900
30	30	2,00	0,55	0,17300
32	32	2,00	0,55	0,18000
35	35	2,00	0,55	0,19700
38	38	1,50	0,45	0,21200
40	40	1,50	0,45	0,22500
42	42	1,50	0,45	0,23700

Original technical data by OCONO - VACUFLEX

Available Through BORSERINI SRL
Via C. Negri 10-12 - 23030 Chiuro (SO) - Italy | +39 0342 209200 | info@borserini.it | www.borserini.com
Registered Office: Via Parolo 38 - 23100 Sondrio (SO) - Italy