VSM AS

Applications vacuum cleaner, industrial vacuum cleaners, cleaning, grinding machines, textile fiber extraction

Structure TPO, black, opaque, profile helix / solid profile helix

Temperature -50°C up to 60°C

Properties smooth inside, corrugated outside, excellent flexibility, permanently antistatic, very good resilience when pressed or twisted



Technical data

Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)
20	28,00	50	0,60	0,60	0,19240
25	33,00	50	0,60	0,60	0,24000
27	35,50	60	0,60	0,60	0,25630
28	36,00	60	0,60	0,60	0,28550
29	37,00	70	0,50	0,50	0,29610
32	40,50	70	0,50	0,50	0,30860
35	43,60	75	0,50	0,50	0,33492
36	43,00	75	0,50	0,50	0,34605
38	48,00	80	0,40	0,40	0,36882
40	50,00	90	0,40	0,40	0,38231
45	55,00	100	0,30	0,30	0,43073
48	58,00	110	0,28	0,28	0,44886
50	61,00	120	0,25	0,25	0,46810
60	72,00	140	0,20	0,20	0,57903
63	74,00	150	0,18	0,18	0,60519
70	81,00	165	0,17	0,17	0,73000
75	87,00	180	0,16	0,16	0,55100
80	92,00	200	0,15	0,15	0,93646

Original technical data by OCONO - VACUFLEX

Available Through BORSERINI SRL
Via C. Negri 10-12 - 23030 Chiuro (SO) - Italy | +39 0342 209200 | info@borserini.it | www.borserini.com
Registered Office: Via Parolo 38 - 23100 Sondrio (SO) - Italy