VSM-EL

Applications industrial vacuum cleaners, vacuum cleaner, cleaning, sawing & milling, textile fiber extraction

Structure TPO, black / jet black (similar RAL 9005), opaque, profile helix / solid profile helix

Temperature -50°C up to 60°C

Properties corrugated outside, smooth inside, excellent flexibility, electrically conductive ($R \leq 10^3$ Ohm) good flexibility restoring force after compression/bending; Norms: ATEX 2014/34/EU



Technical data

Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)
25	33,00	55	0,60	0,60	0,17100
27	35,50	60	0,60	0,60	0,17800
32	40,50	70	0,50	0,50	0,23100
35	42,60	75	0,45	0,50	0,29200
36	43,60	75	0,50	0,45	0,29900
38	48,00	80	0,40	0,40	0,35500
40	51,00	80	0,40	0,40	0,38200
45	56,00	110	0,30	0,30	0,43000
47	58,00	115	0,30	0,30	0,44900
50	61,00	120	0,25	0,25	0,46400
51	62,00	120	0,25	0,25	0,55050
60	72,00	140	0,20	0,20	0,63100
63	75,00	148	0,19	0,19	0,66100
76	87,00	165	0,15	0,15	0,90500

Original technical data by OCONO - VACUFLEX

Available Through BORSERINI SRL
Via C. Negri 10-12 - 23030 Chiuro (SO) - Italy | +39 0342 209200 | info@borserini.it | www.borserini.com
Registered Office: Via Parolo 38 - 23100 Sondrio (SO) - Italy