VSM-H

Applications industrial vacuum cleaners, vacuum cleaner, exhaust gas extraction, extraction systems, automotive engineering

Structure TPE/E, black / jet black (similar RAL 9005), opaque, profile helix / solid profile helix

Temperature -60°C up to 120°C, short term up to 150°C

Properties excellent flexibility, very good temperature resistance, very good low-temperature flexibility, good oil & petrol resistance, good resistance to compressed air containing mineral oil, very good resilience when pressed or twisted, excellent mechanical properties, especially for higher tensile forces



Technical data

Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)
25	33,00	50	0,60	0,60	0,25000
32	40,50	70	0,50	0,50	0,35300
35	43,60	75	0,50	0,50	0,38000
36	44,70	75	0,50	0,50	0,44800
38	48,00	80	0,40	0,40	0,32300
40	50,00	90	0,40	0,40	0,44000
42	53,00	95	0,35	0,35	0,47000
45	55,00	100	0,30	0,30	0,49800
48	59,00	110	0,25	0,25	0,54000
50	61,00	120	0,25	0,25	0,81400
60	72,00	140	0,20	0,20	0,86700
63	74,00	150	0,18	0,18	0,73000
70	81,00	165	0,17	0,17	0,81000
75	87,00	180	0,16	0,16	0,88000
80	92,00	200	0,15	0,15	0,95000

Original technical data by OCONO - VACUFLEX

Available Through BORSERINI SRL
Via C. Negri 10-12 - 23030 Chiuro (SO) - Italy | +39 0342 209200 | info@borserini.it | www.borserini.com
Registered Office: Via Parolo 38 - 23100 Sondrio (SO) - Italy