# VSM-HX



**Applications** exhaust gas extraction, extraction systems, air supply, steam extraction, air extraction

**Structure** TPO, black / jet black (similar RAL 9005), opaque, profile helix / solid profile helix

**Temperature** -60°C up to 180°C, short term up to 250°C

**Properties** excellent flexibility, excellent temperature resistance, good low-temperature flexibility, good oil & petrol resistance, good resistance to compressed air containing mineral oil, good ozone- & UV-resistance, rot proof



## Technical data

| Inner Diameter (mm) | Outer Diameter (mm) | Bending Radius (mm) | Max. Operating Pressure (bar) | Vacuum Max. (bar) | Weight (kg/m) |
|---|---|---|---|---|---|
| 25 | 33,00 | 50 | 0,60 | 0,60 | 0,11000 |
| 32 | 40,50 | 70 | 0,50 | 0,50 | 0,27500 |
| 38 | 48,00 | 80 | 0,40 | 0,40 | 0,32000 |
| 50 | 61,00 | 120 | 0,25 | 0,25 | 0,42000 |

*Original technical data by OCONO - VACUFLEX*

**Available Through BORSERINI SRL**
Via C. Negri 10-12 - 23030 Chiuro (SO) - Italy | +39 0342 209200 | info@borserini.it | www.borserini.com
Registered Office: Via Parolo 38 - 23100 Sondrio (SO) - Italy