VSM-L-SO2

Applications extraction systems, vacuum cleaner, industrial vacuum cleaners, cable protection, exhaust gas extraction

Structure TPO, black / jet black (similar RAL 9005), opaque, profile helix / solid profile helix

Temperature -50°C up to 60°C

Properties excellent flexibility, corrugated outside, smooth inside, crush-resistant, good resistance to compressed air containing mineral oil, good oil & petrol resistance, hydrolysis & microbe resistant, weather proof, good ozone- & UV-resistance, rot proof



Technical data

Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)
27	34,00	45	0,50	0,50	0,15500
29	36,00	45	0,50	0,50	0,16500
32	39,00	50	0,45	0,45	0,18500
38	45,00	55	0,35	0,35	0,22000
50	58,00	75	0,20	0,20	0,28950

Original technical data by OCONO - VACUFLEX

Available Through BORSERINI SRL
Via C. Negri 10-12 - 23030 Chiuro (SO) - Italy | +39 0342 209200 | info@borserini.it | www.borserini.com
Registered Office: Via Parolo 38 - 23100 Sondrio (SO) - Italy