VSM-S01

Applications vacuum cleaner, industrial vacuum cleaners, cleaning, dust extraction, sprayers

Structure TPO, black / grey aluminium (similar RAL 9007), profile helix / solid profile helix

Temperature -50°C up to 60°C

Properties excellent flexibility, crush-resistant, can be driven over, very good chemical resistance, good flexibility restoring force after compression or bending



Technical data

Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)
25	33,00	50	0,60	0,60	0,15030
27	35,50	60	0,60	0,60	0,17040
29	38,50	65	0,60	0,60	0,18270
32	40,50	70	0,50	0,50	0,32700
32	40,50	70	0,50	0,50	0,22900
36	44,70	75	0,50	0,50	0,28907
37	45,10	80	0,50	0,50	0,29500
38	48,00	80	0,40	0,40	0,36230
40	50,00	90	0,40	0,40	0,38140
50	61,00	120	0,25	0,25	0,51630
60	72,00	140	0,20	0,20	0,62660
63	75,00	148	0,19	0,19	0,65457
70	80,00	165	0,17	0,17	0,69000
75	87,00	180	0,16	0,16	0,74000
80	92,00	200	0,15	0,15	0,79000

Original technical data by OCONO - VACUFLEX

Available Through BORSERINI SRL
Via C. Negri 10-12 - 23030 Chiuro (SO) - Italy | +39 0342 209200 | info@borserini.it | www.borserini.com
Registered Office: Via Parolo 38 - 23100 Sondrio (SO) - Italy