VSM

Applications industrial vacuum cleaners, vacuum cleaner, cleaning, sawing & milling, extraction systems

Structure TPO, grey / squirrel grey (similar RAL 7000), opaque, profile helix / solid profile helix

Temperature -50°C up to 60°C

Properties excellent flexibility, very good low-temperature flexibility, smooth inside, corrugated outside, crush-resistant, can be driven over, good flexibility restoring force after compression or bending, excellent mechanical properties, especially for higher tensile forces



Technical data

Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)
13	22,00	40	0,60	0,60	0,07170
25	33,00	50	0,60	0,60	0,24040
28	37,00	64	0,60	0,60	0,27190
29	38,00	65	0,50	0,50	0,28160
32	41,00	70	0,50	0,50	0,30600
35	44,00	75	0,50	0,50	0,35000
36	45,00	75	0,50	0,50	0,38170
37	46,00	80	0,50	0,50	0,36000
38	47,00	80	0,40	0,40	0,40190
40	49,00	90	0,40	0,40	0,39090
45	55,00	100	0,30	0,30	0,43220
50	61,00	120	0,25	0,25	0,47670
51	60,00	120	0,25	0,25	0,48680
60	72,00	140	0,20	0,20	0,57070
63	75,00	143	0,20	0,20	0,57140
70	82,00	165	0,17	0,17	0,72000
75	87,00	180	0,16	0,16	0,74000
76	88,00	180	0,16	0,16	1,08350
80	92,00	200	0,15	0,15	1,31000

Original technical data by OCONO - VACUFLEX

Available Through BORSERINI SRL
Via C. Negri 10-12 - 23030 Chiuro (SO) - Italy | +39 0342 209200 | info@borserini.it | www.borserini.com
Registered Office: Via Parolo 38 - 23100 Sondrio (SO) - Italy